



L1-3 AIR TIP LIFT SPECIFICATIONS	
1.) OPERATING AIR PRESSURE: 90 PSI	
2.) ROTATION: 90 DEGREES	
3.) FILTER, REGULATOR, LUBRICATOR BY OWNER	
4.) HOIST HOOK MUST HAVE SAFETY LATCH	
5.) UNIT FURNISHED WITH AIR QUICK COUPLING	
6.) CONTROL PIPING TO HOIST BY OWNER	
ROLL WIDTH CAP. (LBS.)	
10"	1260
20"	780
30"	560
40"	440

TOLERANCES UNLESS SPECIFIED  
 MACHINED .XXX - ±.005"  
 XX - ±.01"  
 X - ±.05"  
 FRACTIONS - ±1/16"  
 ANGULAR - ±.3°

REV	DATE	BY	CHANGES

**TILT-LOCK**  
 13070 43RD STREET NE  
 ST. MICHAEL, MN 55376  
 PH: 763-447-7045  
 FAX: 763-447-7046

**TITLE: L1-3 AIR TIP-LIFT (MTR) (HMC)**  
**INTERLOCK SWITCH**

DRAWN BY:	DATE:	SCALE:	WEIGHT:
TGK	2/4/03	NONE	X
RELEASED BY:	DWG:		
	TA30046C		B

NOTICE TO PERSONS RECEIVING THIS DRAWING AND/OR TECHNICAL INFORMATION: TILT-LOCK CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING AND/OR TECHNICAL INFORMATION IS ISSUED IN CONFIDENCE FOR ENGINEERING INFORMATION ONLY AND MAY NOT BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, WITHOUT THE WRITTEN PERMISSION FROM TILT-LOCK TO THE USER.

TILT-LOCK IS NOT RESPONSIBLE FOR THE STRENGTH OF BUILDING MEMBERS FINISHED BY OTHERS.