



- L2-3 ELECTRIC TIP LIFT SPECIFICATIONS**
- 1.) POWER REQ: 110VOLT SINGLE PHASE 75AMPS
 - 2.) ROTATION: 90 DEGREES
 - 3.) FILTER, REGULATOR, LUBRICATOR BY OWNER
 - 4.) HOIST HOOK MUST HAVE SAFETY LATCH
 - 5.) UNIT FURNISHED WITH AIR QUICK COUPLING
 - 6.) CONTROL WIRING TO HOIST BY OWNER

| ROLL WIDTH | CAP. (LBS.) |
|------------|-------------|
| 10" | 2000 |
| 20" | 1485 |
| 30" | 1085 |
| 40" | 855 |
| 50" | 705 |
| 60" | 600 |
| 70" | 520 |

TOLERANCES UNLESS SPECIFIED
 MACHINED .XXX - ±.005"
 XX - ±.01"
 X - ±.05"
 FRACTIONS - ±1/16"
 ANGULAR - ±.3°

| REV | DATE | BY | CHANGES |
|-----|-------|-----|------------------------|
| 1 | 11/02 | GLM | ADDED INTERLOCK SWITCH |

TILT-LOCK
 12070 43RD STREET NE
 ST. MICHAEL, MN 55376
 PH: 763-447-7045
 FAX: 763-447-7046

| | | | |
|--|--------------|-------------|-----------|
| TITLE: L2-3 ELEC. TIP LIFT P.T.R AND H.M.C | | | |
| DRAWN BY: TGK | DATE: 4/7/04 | SCALE: NONE | WEIGHT: X |
| RELEASED BY: DMS | TAB3070TC | | SIZE: B |

NOTICE TO PERSONS RECEIVING THIS DRAWING AND/OR TECHNICAL INFORMATION: TILT-LOCK CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED HEREON. THIS DRAWING AND/OR TECHNICAL INFORMATION IS ISSUED IN CONFIDENCE FOR ENGINEERING INFORMATION ONLY AND MAY NOT BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT PERMISSION FROM TILT-LOCK. © THE YEAR

TILT-LOCK IS NOT RESPONSIBLE FOR THE STRENGTH OF BUILDING MEMBERS FINISHED BY OTHERS.