



L2-3 AIR TIP LIFT SPECIFICATIONS	
1.) OPERATING AIR PRESSURE: 90 PSI	
2.) ROTATION: 90 DEGREES	
3.) FILTER, REGULATOR, LUBRICATOR BY OWNER	
4.) HOIST HOOK MUST HAVE SAFETY LATCH	
5.) UNIT FURNISHED WITH AIR QUICK COUPLING	
6.) CONTROL PIPING TO HOIST BY OWNER	
ROLL WIDTH	CAP. (LBS.)
10"	2000
20"	2000
30"	1590
40"	1240
50"	1020

TOLERANCES UNLESS SPECIFIED
MACHINED .XXX - ±.005"

.XX - ±.01"
X - ±.05"

FRACTIONS - ±1/16"
ANGULAR - ±.3°

NOTICE TO PERSONS RECEIVING THIS DRAWING AND/OR TECHNICAL INFORMATION: TILT-LOCK CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED THEREON. THIS DRAWING AND/OR TECHNICAL INFORMATION IS ISSUED IN CONFIDENCE FOR ENGINEERING INFORMATION ONLY AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING SHOWN OR REFERRED TO HEREON WITHOUT DIRECT WRITTEN PERMISSION FROM TILT-LOCK TO THE USER.

TILT-LOCK IS NOT RESPONSIBLE FOR THE STRENGTH OR BUILDING MEMBERS FURNISHED BY OTHERS.

REV	DATE	BY	CHANGES
1	10/02	GLM	Added interlock switch



TILT-LOCK
12070 43RD STREET NE
ST. MICHAEL, MN 55376
PH: 763-497-7045
FAX: 763-497-7046

TITLE:
L2-3 AIR TIP LIFT P.T.R H.M.C

DRAWN BY: TGK	DATE: 2/11/02	SCALE: NONE	WEIGHT: X
RELEASED BY: DWG.	TA30750-001C		SIZE: B
			REV.