



L51-3 ELECTRIC TIP LIFT SPECIFICATIONS

- 1) POWER REQ. 110VOLT SINGLE PHASE 7.5AMPS
- 2) ROTATION: 90 DEGREES
- 3) FILTER REGULATOR LUBRICATOR BY OWNER
- 4) HOIST HOOK MUST HAVE SAFETY LATCH
- 5) UNIT FURNISHED WITH AIR QUICK COUPLING
- 6) CONTROL WIRING TO HOIST BY OWNER

ROLL WIDTH	CAP. (LBS.)
10"	800
20"	500
30"	360
40"	285
50"	235
60"	200
70"	175

TOLERANCES UNLESS SPECIFIED

MACHINED XXX	- ±.005"
XX	- ±.01"
X	- ±.05"
FRACTIONS	- ±1/16"
ANGULAR	- ±.3°

REV.	DATE	BY	CHANGES

TILT-LOCK
 13070 43RD STREET NE
 ST. MICHAEL, MN 55376
 PH: 763-447-7045
 FAX: 763-447-7046

L51-3 ELEC. P.T.R AND H.M.C

TITLE

DRAWN BY:	DATE:	SCALE:	WEIGHT:
TGK	4/7/04	NONE	X
RELEASED BY:	DWG:	TA32127C	
		SIZE:	REV:
		B	

NOTICE TO PERSONS RECEIVING THIS DRAWING AND/OR TECHNICAL INFORMATION: TILT-LOCK CLAIMS PROPRIETARY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING AND/OR TECHNICAL INFORMATION IS ISSUED IN CONFIDENCE FOR ENGINEERING INFORMATION ONLY AND MAY NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT WRITTEN PERMISSION FROM TILT-LOCK TO THE USER.

TILT-LOCK IS NOT RESPONSIBLE FOR THE STRENGTH OF BUILDING MEMBERS FINISHED BY OTHERS.